

Valvola a sfera 3 pz tirantata connessioni a saldare SERIE VSNS326

- Investment Castings for body and Cap
- Internal Entry Blow-Out Proof Stem
- Pressure Rating:1000PSI (PN63)
- Socket Weld:ANSI B16.11,DIN3239
- Working Temperature -25°C+180°C
- Material: CF8M,CF8,CF3M,WCB



- 精密铸造三片式球阀（承插焊）
- 压力等级：1000PSI (PN63)
- 承插焊标准：ANSI B16.11,DIN3239
- 工作温度：-25°C+180°C
- 材质：CF8M,CF8,CF3M,WCB

MATERIAL LIST

ITEM	PART	MATERIAL			QTY
1	BODY	A216-WCB	A351-CF8	A351-CF8M	1
2	BALL	304	304	316	1
3	SEAT	PTFE/RPTFE			2
4	THRUST WASHER	PTFE			1
5	GASKET	PTFE			2
6	PACKING	PTFE			1
7	GLAND NUT	304			1
8	STEM	304	304	316	1
9	SPRING WASHER	304			1
10	NUT	304			1
11	HANDLE	304			1
12	LOCK	304			1
13	HANDLE COVER	PLASTIC			1
14	CAP	A216-WCB	A351-CF8	A351-CF8M	2
15	SPRING WASHER	304	304	304	4 (6)
16	NUT	304			4 (6)
17	BOLT	304	304	304	4 (6)

DIMENSION TABLE

SIZE	Φd	L	H	P	D	W	N.M	KGS
DN6	1/4"	12.5	51	43.5	9.6	14.1	103	0.29
DN10	3/8"	12.5	51	44.5	9.6	17.6	103	0.29
DN15	1/2"	15	63	50	9.6	21.7	103	0.43
DN20	3/4"	20	71	59	12.7	27.1	127	0.61
DN25	1"	25	80	61	12.7	33.8	127	0.80
DN32	1-1/4"	32	94	79	12.7	42.5	154	1.43
DN40	1-1/2"	38	103	83	12.7	48.6	154	1.73
DN50	2"	50	126	94	15.8	61.1	195	2.72
DN65	2-1/2"	65	158	135	15.8	77	244	5.44
DN80	3"	76	179	144	24	90	244	7.64
DN100	4"	94	213	149	24	115.2	285	15.78

